

2360 LED

LED Suspended luminaire

- VDU workstation compliant (UGR < 16)
- Direct/ indirect illumination

The 2360 LED is the smart suspended luminaire for standard-compliant lighting e.g. in offices, meeting rooms, banks, schools and educational facilities. This will get the job done!

Why you'll do a great job with the 2360 LED surface-mounted luminaire

- Pleasant light effect thanks to uniform illumination with direct and indirect portion
- Especially for VDU workstations (UGR < 16)
- 1:1 replacement of conventional luminaires offering time and cost savings during refurbishment
- High efficiency (115 lm/W) and solid service life (50,000 h, L65)
- Attractive price/performance ratio

2360 LED at a glance

Dimensions (L x B x H):	H1: 1,195 x 295 x 16 mm H2: 1,495 x 295 x 20 mm
Luminaire luminous flux:	H1: 4,400 lm H2: 6,000 lm
Colour rendering/-temperature:	Ra > 80 / 3,000K, 4,000 K
Connected load:	H1: 40 W H2: 52 W
Protection rating, safety class:	IP20 / IK02 / I
Weight:	H1: 5.3 kg H2: 6.0 kg

All versions of 2360 LED

Product reference	TOC	Luminous flux [lm]	Wattage [W]	Light colour [K]	Dimensions LxWxH [mm]	Replacement
DALI dimmable						
2360 H1 PW19-IL 4000-830 ETDD	7377551	4,400	40	3,000	1,195 x 295 x 16	1 x 54 W / 2 x 28 W
2360 H1 PW19-IL 4000-840 ETDD	7377651	4,400	40	4,000	1,195 x 295 x 16	1 x 54 W / 2 x 28 W
2360 H2 PW19-IL 6000-830 ETDD	7789951	6,000	55	3,000	1,496 x 295 x 20	2 x 35 W
2360 H2 PW19-IL 6000-840 ETDD	7790051	6,000	55	4,000	1,496 x 295 x 20	2 x 35 W
Switchable						
2360 H1 PW19-IL 4000-830 ET	7377540	4,400	40	3,000	1,195 x 295 x 16	1 x 54 W / 2 x 28 W
2360 H1 PW19-IL 4000-840 ET	7377640	4,400	40	4,000	1,195 x 295 x 16	1 x 54 W / 2 x 28 W
2360 H2 PW19-IL 6000-830 ET	7789940	6,000	55	3,000	1,496 x 295 x 20	2 x 35 W
2360 H2 PW19-IL 6000-840 ET	7790040	6,000	55	4,000	1,496 x 295 x 20	2 x 35 W